

JOINTS

Single Sphere Rubber Joint

PN10/PN16

REEP brand RFJ005 are with wide temperature adaptation, good anti-corrosion ability, high endurance of pressure, prolonged life, good flexibilities. It can be used in various fields of industries from petrochemical, metallurgical, construction, paper, food, electronics and aeronautical.

Material Specification

Component	Material	EN and/or (DIN/ASTM)	
Rubber	EPDM/NBR		
Flange	Steel/Steel Stainless		
Reinforcing Ring	Carbon Steel		

Options

- Other materials, pressure rating, flange connection and larger sizes available upon request.

REEP



• Fig. RFJ005

- DN 32 - 1000
- Pressure rating PN 10 - 16
- Max. working temperature: 115 °C
- Various materials available
- Custom made available

公称通径 DN		长血L (mm)	螺栓数 n	螺栓孔直径 d.(mm)	螺栓孔中心 圆直径D1 (mm)	轴向位移 (mm)		横向位移 (mm)	偏向角度
(mm)	(寸in.)					伸长	压缩		
32	(1 1/4)	95	4	17.5	100	6	9	9	15°
40	(1 1/2)	95	4	17.5	110	6	10	9	15°
50	(2)	105	4	17.5	125	7	10	10	15°
65	(2 1/2)	115	4	17.5	145	7	13	11	15°
80	(3)	130	8	17.5	160	8	15	12	15°
100	(4)	150	8	17.5	180	10	19	13	15°
125	(5)	165	8	17.5	210	12	19	13	15°
150	(6)	180	8	22	240	12	20	14	15°
200	(8)	190	8	22	295	16	25	22	15°
250	(10)	230	12	22	350	16	25	22	15°
300	(12)	254	12	22	400	16	25	22	15°
350	(14)	260	16	22	460	16	25	22	15°
400	(16)	260	16	26	515	16	25	22	15°
450	(18)	260	20	26	565	16	25	22	15°
500	(20)	260	20	26	620	16	25	22	15°
600	(24)	260	20	30	725	16	25	22	15°
700	(28)	260	24	30	840	16	25	22	10°
800	(32)	260	24	33	950	16	25	22	10°
900	(36)	260	28	33	1050	16	25	22	10°
1000	(40)	260	28	36	1160	16	25	22	10°

